

# 0.6Ω Quad SPST Analog Switch 4-Channel 1:1 Multiplexer – Demultiplexer

## FEATURES

- **Bandwidth: 30MHz**
- **High Speed, Typically 50ns**
- **Supply Range: +1.8V to +5.5V**
- **Low ON-State Resistance, 0.6Ω(TYP)**
- **Break-Before-Make Switching**
- **Rail-to-Rail Operation**
- **TTL/CMOS Compatible**
- **Extended Industrial Temperature Range: -40°C to +125°C**

## APPLICATIONS

- **Video Switching**
- **Relay Replacements**
- **USB Switching**
- **Battery-Operated Equipment**
- **Cell Phones**

## DESCRIPTION

The RS2259B is a bidirectional 4-channel single-pole single-throw (SPST) analog switch, which is designed to operate from 1.8V to 5.5V.

The RS2259B device can handle both analog and digital signals. It features bandwidth (30MHz) and low on-resistance (0.6Ω TYP).


Applications include signal gating, chopping, modulation or demodulation (modem), and signal multiplexing for analog-to-digital and digital-to-analog conversion systems.

### Device Information <sup>(1)</sup>

PART NUMBER	PACKAGE	BODY SIZE (NOM)
RS2259B	TSSOP16	5.00mmx4.40mm

(1) For all available packages, see the orderable addendum at the end of the data sheet.

### Functional Block Diagram




## Revision History

Note: Page numbers for previous revisions may differ from page numbers in the current version.

VERSION	Change Date	Change Item
C.2.1	2024/03/07	1. Added the TAPE AND REEL INFORMATION 2. Change Thermal Information on Page 3@RevC.2 3. Modify packaging naming

## PIN CONFIGURATIONS(Top View)



### PIN DESCRIPTION

NAME	PIN	FUNCTION
VCC	13	Power Supply
GND	5	Ground
INx	1,8,9,16	Digital Control Pin
COMx	2,7,10,15	Common Terminal
NOx	3,6,11,14	Normally-Open Terminal
N.C	4,12	No internet connection

### FUNCTION TABLE

INx	NOx
1	All Channels ON
0	All Channels OFF

## SPECIFICATIONS

### Absolute Maximum Ratings

Over operating free-air temperature range (unless otherwise noted) <sup>(1)</sup>

SYMBOL	PARAMETER	MIN	MAX	UNIT
V <sub>+</sub>	Supply Voltage	-0.3	6	V
V <sub>IN</sub>	Input Voltage (All inputs)	-0.3	(V <sub>+</sub> )+0.3	
I <sub>IN</sub>	Continuous Current COM or NO	-500	+500	mA
I <sub>PEAK</sub>	Peak Current COM or NO	-800	+800	
T <sub>J</sub>	Junction Temperature	-40	150	°C
T <sub>stg</sub>	Storage temperature	-65	+150	

(1) Stresses above these ratings may cause permanent damage. Exposure to absolute maximum conditions for extended periods may degrade device reliability. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those specified is not implied.

### ESD Ratings

			VALUE	UNIT
V <sub>(ESD)</sub>	Electrostatic discharge	Human-body model (HBM)	±1000	V
		Machine Model (MM)	±100	V

### Recommended Operating Conditions

Over operating free-air temperature range (unless otherwise noted)

SYMBOL	PARAMETER	MIN	MAX	UNIT
V <sub>CC</sub>	Supply Voltage	1.8	5.5	V
T <sub>A</sub>	Operating temperature	-40	+125	°C

### Thermal Information

THERMAL METRIC		RS225B	UNIT
		16 PINS	
		TSSOP16	
R <sub>θJA</sub>	Junction-to-ambient thermal resistance	110	°C/W
R <sub>θJC(top)</sub>	Junction-to-case(top) thermal resistance	45.3	°C/W
R <sub>θJB</sub>	Junction-to-board thermal resistance	56.9	°C/W
Ψ <sub>JT</sub>	Junction-to-top characterization parameter	5.4	°C/W
Ψ <sub>JB</sub>	Junction-to-board characterization parameter	56.3	°C/W
R <sub>θJC(bot)</sub>	Junction-to-case(bottom) thermal resistance	N/A	°C/W

**PACKAGE/ORDERING INFORMATION**

PRODUCT	ORDERING NUMBER	TEMPERATURE RANGE	PACKAGE LEAD	PACKAGE MARKING <sup>(1)</sup>	PACKAGE OPTION
RS2259B	RS2259BXTSS16	-40°C ~125°C	TSSOP16	RS2259B	Tape and Reel,4000

NOTE:

(1) There may be additional marking, which relates to the lot trace code information (data code and vendor code), the logo or the environmental category on the device.

## ELECTRICAL CHARACTERISTICS

$V_{CC} = 5.0\text{ V}$ ,  $T_A = -40^\circ\text{C}$  to  $125^\circ\text{C}$  (unless otherwise noted)

PARAMETER	SYMBOL	CONDITIONS	$V_{CC}$	$T_A$	MIN	TYP	MAX	UNIT
<b>ANALOG SWITCH</b>								
Analog Signal Range	$V_{COM}, V_{NO}$			FULL	0		$V_{CC}$	V
On-Resistance	$R_{ON}$	$V_{NO} = V_{CC}/2$ , $I_{COM} = -10\text{mA}$ , Switch ON, See Figure 4	5V	+25°C		0.6	1.0	$\Omega$
				FULL			1.2	$\Omega$
			3.3V	+25°C		1.0	1.5	$\Omega$
				FULL			1.7	$\Omega$
On-Resistance Match Between Channels	$\Delta R_{ON}$	$V_{NO} = V_{CC}/2$ , $I_{COM} = -10\text{mA}$ , Switch ON, See Figure 4	5V	+25°C		0.04	0.1	$\Omega$
				FULL			0.12	$\Omega$
			3.3V	+25°C		0.04	0.1	$\Omega$
				FULL			0.12	$\Omega$
On-Resistance Flatness	$R_{FLAT(ON)}$	$0 \leq (V_{NO}) \leq V_{CC}/2$ , $I_{COM} = -10\text{mA}$ , Switch ON, See Figure 4	5V	+25°C		0.18	0.3	$\Omega$
				FULL			0.4	$\Omega$
			3.3V	+25°C		0.54	0.7	$\Omega$
				FULL			0.8	$\Omega$
NO, COM OFF Leakage Current	$I_{NO(OFF)}, I_{COM(OFF)}$	$V_{COM} = 0.3\text{V}$ , $V_{CC}/2$ $V_{NO} = V_{CC}/2$ , $0.3\text{V}$ See Figure 5	1.8 to 5.5V	FULL			1	$\mu\text{A}$
NO, COM ON Leakage Current	$I_{NO(ON)}, I_{COM(ON)}$	$V_{COM} = 0.3\text{V}$ , Open $V_{NO} = \text{Open}$ , $0.3\text{V}$ See Figure 6	1.8 to 5.5V	FULL			1	$\mu\text{A}$
<b>DIGITAL CONTROL INPUTS<sup>(1)</sup></b>								
Input High Voltage	$V_{IH}$		5V	FULL	1.5			V
			3.3V	FULL	1.3			V
Input Low Voltage	$V_{IL}$		5V	FULL			0.6	V
			3.3V	FULL			0.5	V
Input Leakage Current	$I_{IN}$	$V_{IN} = V_{IO}$ or 0	1.8 to 5.5V	FULL			1	$\mu\text{A}$

(1) All unused digital inputs of the device must be held at  $V_{IO}$  or GND to ensure proper device operation.

**ELECTRICAL CHARACTERISTICS (continued)**
 $V_{CC} = 5.0\text{ V}$ ,  $T_A = -40^\circ\text{C}$  to  $125^\circ\text{C}$  (unless otherwise noted)

PARAMETER	SYMBOL	CONDITIONS	$V_{CC}$	$T_A$	MIN	TYP	MAX	UNIT
<b>DYNAMIC CHARACTERISTICS</b>								
Turn-On Time	$t_{ON}$	$V_{NO} = V_{CC}$ , $R_L = 300\Omega$ , $C_L = 35\text{pF}$ , See Figure 7	5V	+25°C		50		ns
			3.3V			50		
Turn-Off Time	$t_{OFF}$	$V_{NO} = V_{CC}$ , $R_L = 300\Omega$ , $C_L = 35\text{pF}$ , See Figure 7	5V	+25°C		15		ns
			3.3V			17		
Break-Before-Make Time Delay	$t_{BBM}$	$V_{NO} = 3\text{V}$ , $R_L = 300\Omega$ , $C_L = 35\text{pF}$ , See Figure 8	5V	+25°C		10		ns
			3.3V			11		
Off Isolation	$O_{ISO}$	$R_L = 50\Omega$ , Switch OFF, See Figure 10	$f = 10\text{MHz}$	+25°C		-68		dB
			$f = 1\text{MHz}$	+25°C		-86		dB
-3dB Bandwidth	BW	Switch ON, $R_L = 50\Omega$ See Figure 9		+25°C		30		MHz
NO, COM OFF Capacitance	$C_{NO(OFF)}$ , $C_{COM(OFF)}$	$V_{NO} = V_{CC}/2$ or GND, Switch OFF		+25°C		80		pF
NO, COM ON Capacitance	$C_{NO(ON)}$ , $C_{COM(ON)}$	$V_{NO} = V_{CC}/2$ or GND, Switch ON		+25°C		350		pF
<b>POWER REQUIREMENTS</b>								
Power Supply Range	$V_{CC}$			FULL	1.8		5.5	V
Power Supply Current	$I_{CC}$	$V_{IN} = \text{GND}$ or $V_{CC}$	5.5V	FULL			1	$\mu\text{A}$

### TYPICAL CHARACTERISTICS




Figure 1. Bandwidth vs Frequency




Figure 2. Bandwidth vs Frequency






Figure 3. Typical Ron as a Function of Input Voltage




### Parameter Measurement Information



**Figure 4. ON-State Resistance ( $R_{ON}$ )**



**Figure 5. OFF-State Leakage Current ( $I_{COM(OFF)}$ ,  $I_{NO(OFF)}$ )**



**Figure 6. ON-State Leakage Current ( $I_{COM(ON)}$ ,  $I_{NO(ON)}$ )**




Figure 7. Turn-On ( $t_{ON}$ ) and Turn-Off Time ( $t_{OFF}$ )




Figure 8. Break-Before-Make Time ( $t_{BBM}$ )




Figure 9. Bandwidth (BW)




Figure 10. OFF Isolation ( $O_{ISO}$ )




Figure 11. Crosstalk ( $X_{TALK}$ )





Figure 12. Charge Injection ( $Q_C$ )


# PACKAGE OUTLINE DIMENSIONS

## TSSOP16



RECOMMENDED LAND PATTERN (Unit: mm)

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A		1.200		0.047
A1	0.050	0.150	0.002	0.006
A2	0.800	1.050	0.031	0.041
b	0.190	0.300	0.007	0.012
c	0.090	0.200	0.004	0.008
D	4.860	5.100	0.191	0.201
E	4.300	4.500	0.169	0.177
E1	6.200	6.600	0.244	0.260
e	0.650(BSC)		0.026(BSC)	
L	0.500	0.700	0.02	0.028
H	0.25TYP		0.01TYP	
$\theta$	1°	7°	1°	7°

**TAPE AND REEL INFORMATION**  
**REEL DIMENSIONS**
**TAPE DIMENSION**


NOTE: The picture is only for reference. Please make the object as the standard.

**KEY PARAMETER LIST OF TAPE AND REEL**

Package Type	Reel Diameter	Reel Width(mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
TSSOP16	13"	12.4	6.90	5.60	1.20	4.0	8.0	2.0	12.0	Q1